SMG Integrated Media Gateway

Remove Unclearness, Disconnection and Complexity



SMG 3000

- Compact 1U form factor for 8/16 E1/T1-SIP
- Compliant with SS7/SS1/ISDN Globally
- Telecom Resilience and Voice Quality

With a better way to interconnect and deliver services through ease-of-use and unmatched low total cost of ownership, The Synway SMG3000 is a member of Synway's gateway family that enables service providers and enterprises to maximize value of their networks and services. The SMG3000 converts digital PSTN message into IP formats and connects and secures sessions across IP and mixed network boundaries to support the seamless delivery of services.

Besides providing low-to-high scalability in single compact footprint, the SMG3000 processes signaling and media in a single chassis and can deliver SIP services into SS1, SS7, PRI, and SIP networks. It also provides basic IP session control and security features to help service providers deliver multimedia services with features that include SIP trunking support, and IP-to-IP transcoding of voice, mobile HD voice.

The SMG3000 connects IP and hybrid networks via telephony and Ethernet links in a compact 1U form factor appliance. It also transforms media and signaling to support efficient and reliable voice, fax and multimedia sessions for mobile, fixed and cloud-based applications. The convergence of IP multimedia and TDM gateway functionality in a single chassis in the SMG offers significant reductions in investment and operational cost when compared to less integrated alternatives.

Key features

PARKEALU UANTUNE 1 2 7 9 11 13 15 ACT LINK LINK 2 4 4 10 13 14 18 COMMAN

Flexible and efficient Gateway Solution

With its scalable density and versatility, SMG can help enable wireless and wireline service providers to add new Value Added Services (VAS) quickly, and provide a clear migration path to an all-IP network.It can scale up to 480 simultaneous IP sessions and at the same time provide media transcoding and impressive sessions per second performance.

SMG supports voice densities ranging from 240 to 480 channels of SS7 signaling, call routing, call translation and IP transcoding in a single 1U chassis for gateway operations. The integrated gateway functionality not only provides interworking between IP and TDM domains, but also automated failover from IP to TDM for outbound routing. These features help service providers looking to improve network and routing resiliency and lower TCO. These capabilities make the SMG an excellent option for mobile VAS, SIP trunking, contact center and emergency service deployments, as well as for retail,wholesale, business, and enhanced Voice over IP (VoIP) services.

Any-to-Any Signaling and Multimedia Connectivity

SMG3000 provides any-to-any network connectivity

through its ability to interwork multiple protocols used by telecommunications providers to deliver services to their retail, business and wholesale customers. it can provide interworking between SS1,R2,ISDN,SS7,SIP formats.

synwa

The SMG also supports any-to-any media transcoding for popular voice codecs. T.38 and G.711 fax interworking and support for RTP, INBAND and SIPINFO method based tones and event handling complement the media transcoding capabilities to provide a high degree of flexibility to help deliver value added services economically.

User-friendly management and configuration toolkits

The Web graphical user interface (WebUI) is a real-time web toolkits to configure, monitor SMG. It allows operators to configure and perform real-time monitoring and maintenance. Flexible SIP and Protocols configuration enable services providers and enterprises to seamlessly connect in hybrid networks, Helping configure SIP, SIP trunking, SIP Mediation, PCM, SS7 and ISDN, Routing and more; And a broad range of gateway toolkits also help gateway's maintenance and software upgrading for Web UI, gateway services and firmware.





E1 Interface



Minimize heating and EMC via regular hexagon cooling hole



Make connections between networks, services and subscribers reliable and efficient

Key Features	Values
Flexible SIP and Protocols configuration enable services providers and enterprises to seamlessly connect in hybrid networks	Help configure SIP, SIP trunking,SIP Mediation, PCM, SS7 and SS1, R2,ISDN, Routing and more; a broad range of gateway toolkits help gateway's maintainance and software upgrading for Web UI,gateway services and firmware
Scalable from 240 to 480 simultaneous SIP sessions with multimedia transcoding, and 240 to 480 channels of SS7 signaling	Scalable IP and TDM connectivity solution provides high performance in a small footprint to help lower ownership cost and operational cost
Combined IP and TDM gateway features on a single platform	Integrated multimedia gateway features facilitate TDM and IP interworking to provide service delivery flexibility and automated failover between domains
Any-to-any signaling and media support	Support for SS1, R2, SS7, SIP signaling, and SIP interworking along with voice and transcoding provides a cost-effective platform to help service providers evolve from a TDM to an all-IP environment
SIP profiler and web based user configuration	Easy-to-use service configuration and management tools can help accelerate service deployment and simplify platform management
Integrated transcoding support for voice, tone and faxing	Eliminates the need to add separate hardware to support transcoding requirements helping to reduce CAPEX and number of platforms deployed
Carrier class solution	Carrier class design and features provide high availability, reliable throughput and enhanced service delivery



Product models

SMG3008	8E1/T1 and 240 SIP channels
SMG3016	16E1/T1 and 480 SIP channels

Routing Features

Call routing and translation(from PCM to IP or reversely)

IP Bearer Features

Coder support: G.711,G.711U,G.729A/B,722,723,GSM,iLBC,Silk,OPUS RFC2833,RF3261,SIPINFO, INBOUND Compliant with TCP/UDP, HTTP, ARP/RARP,DNS,NTP,TFTP,TELNET,STUN and more IP protocols Echo cancellation: G.168 128 ms tail length Voice activity detection and packet loss concealment Comfort noise generation T.38 real-time fax, T.38 – G.711 interworking Digit transmission via RFC 2833 (SIP) Hosted NAT

OAM&P

Network Time Protocol (NTP) Web User Interface (WebUI) supports configuration via browser SNMP MIBs TR069

Power Requirements

AC Power Supply Range 100 – 240 VAC The power supply will operate at frequencies between 47 Hz and 63 Hz

Power Consumption

Typical	Minimum
8 E1/T1	120 Watts
16 E1/T1	150 Watts

Environment

Operating temperature range 0 to +55 °C, 8-90% relative humidity non-condensing Storage temperature range -20 to +85 °C, 8-90% relative humidity non-condensing

Physical Dimensions

 High
 Wide
 Deep

 1.72 in (44 mm)
 17.32in (440 mm)
 10.51in (267 mm)

 Weight 6.8 lb (Approx.3.1 kg)
 10.51in (267 mm)
 10.51in (267 mm)

Maintenance

Power supplies field installation

Resiliency

SS7 signaling: 1+1 active/standby redundancy Redundant power supply(Dual power system) Smart IP probing Automated failover (Ethernet links) Failover via automatic protection switching

Capacity

240 - 480 TDM channels per 1U shelf 240 - 480 VoIP channels per 1U shelf

I/O Interfaces — Rear I/O — T1/E1

Telephony	8/16T1/E1 for timing (BITS clock), signaling and
T1 and E1	bearer traffic
	(T1 - 100 ohms and E1 - 120 ohms)
Clock Sync	Stratum

IP Interfaces

IP Dual redundant 2 - 100/1000 Base-T Ethernet for VoIP payload and signaling

Gateway Memory

Flash 256M, System memory 2G

TDM Signaling Protocols

E1 Mode:

- E1-Euro ISDN , E1-NI2 ISDN , E1-Q.Sig, E1-CAS, E1-MFCR2
- T1 Mode:
- T1-NI2 ISDN, T1 5ESS 9 ISDN, T1 5ESS 10 ISDN, T1 DMS100 ISDN,
- T1 DMS 100 Meridian ISDN,T1 QSIG,
- 16 SS7 links in standalone configuration

IP Protocols

Core SIP Specifications and Notable Extensions RFC 3261 SIP Basic RFC 3262 SIP PRACK RFC 3265 SIP Subscribe/Notify RFC2833,RF3261,2976,3515,3581,SIPINFO,INBOUND

Notable SIP Extensions

RFC 3398 ISUP/SIP Mapping RFC 3711 SRTP (for SIP) Tel URI – RFC 3966 IP and ISUP interworking and more

QoS

Adaptive jitter buffer Packet loss compensation Configurable Type of Service (ToS) fields for packet prioritization and routing

Approvals and Compliance

For information about RoHS compliance and other approvals, please contact Synway directly.

EMC/EMI

Compliant with most international standards. For compliance documents, please contact Synway's sales representatives.

Safety

Compliant with most international standards, please ask Synway or its sales representatives worldwide. Synway would comply all new safety standardfor different regions around the world while needed.

Telecom Approvals

(Partially approved)Compliant with most international standards, please ask Synway or its sales representatives worldwide.





Synway Information Engineering Co., Ltd. Synway R&D Building No.3756, Nanhuan Road, Binjiang Hangzhou, 310053, China TEL: +86 571 88860561 FAX: +86 571 88850923 HTTP://www.synway.net EMAIL: sales@synway.net

No notice for any change in future in this catalog, For more information or lates update, please visit Synway website. Synway has made efforts to ensure the accuracy of this documents, however, due to the ongoing improvements and revisions to our products, Synway can not guarantee the accuracy of the material after the date of publication, or accept responsibility for errors or omissions. Revised documents may be published when deemed necessary by Synway.